

**DPG**

# AW 46 HYDRAULIC OIL

### PRODUCT DESCRIPTION

DPG AW 46 Hydraulic Oil is specifically designed for use in high-pressure systems which require greater wear protection and deposit control than that provided by standard antiwear hydraulic fluids. DPG AW 46 Hydraulic Oil is specially formulated with proprietary additive chemistry and hydrocracked base oils. DPG AW 46 Hydraulic Oil is recommended for use in a variety of high-pressure mobile and stationary hydraulic systems utilizing vane, piston or gear pumps.

DPG AW 46 Hydraulic Oil is tested and approved by Denison Hydraulics in accordance with its premium HF-0 requirements. DPG AW 46 Hydraulic Oil exceeds Vickers M-2950-S, Vickers F-286-S and U.S. Steel 127 and 136 requirements.

Refer to the Product Information Sheet and Material Safety Data Sheet for additional information.

### CAUTION!

Overexposure to product may cause eye, skin, or respiratory tract irritation or damage.

### PRECAUTIONS:

Keep away from heat, sparks, and open flame. **DO NOT** get in eyes. Minimize contact with skin or clothing. Minimize breathing mists or vapors. Use only with adequate ventilation. Keep container closed when not in use. Wash thoroughly after handling. Keep out of reach of children.

### FIRE FIGHTING:

Use waterspray to keep fire-exposed surfaces cool. Extinguish with Foam, Waterspray, Dry Chemical, Carbon Dioxide, or Vaporizing Liquid.

### FIRST AID:

**EYES:** Flush with water until irritation subsides; if irritation persists, seek medical attention. **SKIN:** Remove contaminated clothing and shoes. Wash with soap and water; if irritation persists, seek medical attention. **INGESTION:** If swallowed, **DO NOT INDUCE VOMITING.** Keep at rest; get prompt medical attention. **INHALATION:** If overcome or affected by hot product, remove victim from exposure. Use artificial respiration if not breathing.

### PILL CONTROL:


Eliminate all ignition sources. Ventilate confined spaces. Keep public away. Recover free product. Add Sand, Earth or other suitable absorbent to spill area. Keep product out of sewers and water courses. Advise authorities if product cannot be contained. Conform with applicable governmental regulations.

### DANGER

\*Empty containers retain residue (liquid and/or vapor) and can be dangerous. **DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE THIS CONTAINER TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; IT MAY EXPLODE AND CAUSE INJURY OR DEATH.** Do not attempt to clean since residue is difficult to remove. "Empty" containers should be completely drained, properly bunged and promptly returned to a container reconditioner. Dispose of "empty" containers in accordance with your local, state and government regulations.

### HMIS RATING

HEALTH 1  
FLAMMABILITY 1  
REACTIVITY 0



BATCH NUMBER	IN CASE OF EMERGENCY CONTACT	NET CONTENTS	COMMENTS
<b>092503</b>	<b>CHEMTREC 1-800-424-9300</b>	<b>55 GALLONS</b>	<b>FILTERED</b>

REFER TO PRODUCT INFORMATION SHEET AND MATERIAL SAFETY DATA SHEET FOR FURTHER INFORMATION  
KEEP OUT OF REACH OF CHILDREN - FOR INDUSTRIAL / PROFESSIONAL USE ONLY

Demag Plastics Group, makes no warranty, either express or implied, as to the quality, merchantability or fitness for any particular purpose of any products referred to and except as hereinafter stated, makes no guarantee of results or of satisfaction from reliance upon the information or recommendation set forth. The buyer's or user's sole and exclusive remedy and Demag Plastics Group's sole limit of liability from any losses resulting from the use of said product shall be for to the purchase price of the product causing the loss. For further information contact Demag Plastics Group, Strongsville, Ohio (866) 491-1045.

**DPG**

# AW 46 HYDRAULIC OIL

### HMIS RATING

HEALTH 1  
FLAMMABILITY 1  
REACTIVITY 0

